

DG2-800(2V800Ah)



Specification







DG (Deep Cycle GEL) series is pure GEL battery with 20 years floating design life , it is ideal for standby or frequent cyclic discharge applications under extreme environments. By using strong grids, high purity lead and patented GEL electrolyte, the DG series offers excellent recovery capability after deep discharge under frequent cyclic discharge use, and it can offers 2 times cyclic life than the standard series. It is suitable for solar & wind system, marine, deep discharge UPS etc.



Cells Per Unit	1
Voltage Per Unit	2
Capacity	800Ah@10hr-rate to 1.80V per cell @25°C
Weight	Approx. 50.0 Kg (Tolerance ±3.0%)
Internal Resistance	Approx. 0.60 mΩ
Terminal	F10(M8)
Max. Discharge Current	3200A (5 sec)
Design Life	20 years (floating charge)
Maximum Charging Current	160.0 A
Reference Capacity	C3 624.0AH C5 692.0AH C10 800.0AH C20 848.0AH
Float Charging Voltage	2.27 V~2.30 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	2.37 V~2.40 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -40°C~60°C Charge: -20°C~50°C Storage: -40°C~60°C
Normal Operating Temperature Range	25°C ±5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 2% at 20°C. Please charged batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.

Dimensions



Length	383±2mm (15.1 inches)
Width	171±2mm (6.73 inches)
Height	330±2mm (13.0 inches)
Total Height	342±2mm (13.5 inches)
Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m

Unit: mm

Constant Current Discharge Characteristics : A(25°C)

F.V/Time	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	6HR	8HR	10HR	20HR
1.60V	1010	782.4	523.2	320.8	234.4	180.0	144.0	130.4	106.4	83.2	44.8
1.65V	960.8	751.2	516.8	309.6	224.8	176.0	142.4	127.2	101.6	82.4	44.0
1.70V	896.0	708.0	507.2	304.8	219.2	172.0	140.0	124.0	100.0	81.6	43.2
1.75V	795.2	636.8	466.4	288.0	208.0	166.4	138.4	117.6	96.8	80.8	42.4
1.80V	684.8	580.0	440.0	274.4	200.0	160.0	136.0	116.0	95.2	80.0	41.6
1.85V	579.2	522.4	406.4	259.2	190.4	156.0	128.0	109.6	90.4	77.6	39.2

Constant Power Discharge Characteristics : WPC(25°C)

F.V/Time	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	6HR	8HR	10HR	20HR
1.60V	1769	1426	974.4	600.8	436.8	316.8	285.6	251.2	202.4	165.6	89.6
1.65V	1722	1418	968.8	592.0	428.0	312.0	283.2	248.0	200.8	164.0	88.0
1.70V	1627	1342	959.2	583.2	421.6	311.2	280.0	242.4	197.6	163.2	86.4
1.75V	1449	1210	900.0	552.8	406.4	295.2	276.0	230.4	191.2	161.6	84.8
1.80V	1254	1103	856.0	527.2	389.6	294.4	271.2	227.2	188.0	160.0	83.2
1.85V	1070	994.4	793.6	499.2	371.2	272.8	256.0	215.2	178.4	155.2	78.4


(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values.

The battery must be fully charged before the capacity test. The C₁₀ should reach 95% after the first cycle and 100% after the third cycle.


DG2-800(2V800Ah)




Discharge Characteristics Curve




Charge Characteristic Curve for Cycle Use(IU)




Cycle Life in Relation to Depth of Discharge




Relationship Between Charging Voltage and Temperature




Temperature Effects on Capacity




Storage Characteristics



Effect of Temperature on Long Term Life



Relationship of OCV And State of Charge(20°C)



(Note) All above information shall be changed without prior notice, Ritar reserves the right to explain and update the latest information.