



HR12-570W(12V570W)

Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	570W@15min-rate to 1.67V per cell @25°C
Weight	Approx. 46.0 Kg (Tolerance ±3.0%)
Internal Resistance	Approx. 3.8 mΩ
Terminal	F12(M8)
Max. Discharge Current	1500A (5 sec)
Short Circuit Current	3100A
Design Life	15 years
Max. Charging Current	45.0 A
Reference Capacity	C10 141.5AH C20 150.0AH
Standby Use Voltage	13.6 V~13.8 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Equalization Voltage	14.6 V~14.8 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ±5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



HR (High Rate) series Valve Regulated Lead Acid (VRLA) battery is designed for heavy load discharge applications with 15 years design life in float service. By using strong grids, thick plate and specially designed active material. It is with lower I.R, lower self discharge rate, high power, and longer service life. The HR series battery offers 30% more power output than the standard series. It is suitable for high power standby used, such as datacenter, UPS, EPS etc.



ISO 9001



ISO 14001







OHSAS 18001



MH 28539



Dimensions



F 12 Terminal

Length	483±2mm (19.0 inches)
Width	170±2mm (6.69 inches)
Height	241±2mm (9.49 inches)
Total Height	241±2mm (9.49 inches)
Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m

Unit: mm

Constant Current Discharge Characteristics : A (25°C)

F.V/T ime	5MIN	8MIN	10MIN	15MIN	20MIN	30MIN	60MIN	90MIN
1.60V	467.1	414.9	384.2	315.2	256.7	189.2	109.5	78.6
1.67V	423.8	380.5	355.1	293.9	241.3	179.0	104.4	75.4
1.70V	405.8	365.7	342.3	285.0	234.5	174.7	102.4	73.9
1.75V	374.7	340.7	320.9	269.6	222.8	167.3	98.8	71.6
1.80V	343.3	315.5	299.5	255.1	212.3	160.2	95.2	69.3
1.85V	294.6	268.8	253.8	219.4	184.3	141.7	86.0	63.1

Constant Power Discharge Characteristics : WPC (25°C)

F.V/T ime	5MIN	8MIN	10MIN	15MIN	20MIN	30MIN	60MIN	90MIN
1.60V	858.2	772.7	722.7	600.8	493.3	367.6	205.6	148.7
1.67V	798.8	724.9	682.0	570.0	470.8	352.5	197.9	143.8
1.70V	772.5	703.2	663.0	556.8	460.6	345.4	194.6	141.7
1.75V	724.9	664.5	629.7	532.7	442.1	334.0	189.3	137.9
1.80V	674.7	623.8	594.6	509.0	425.5	322.3	183.7	134.1
1.85V	587.7	538.8	510.5	442.5	372.8	287.5	167.0	123.4

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values.

HR12-570W(12V570W)



Discharge Characteristics Curve




Charge Characteristic Curve For Standby Use




Storage Characteristics




Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity




Relationship of OCV And State of Charge(20°C)



Effect Of Temperature On Long Term Life



Life Characteristics Of Standby Use



(Note) All above information shall be changed without prior notice, Ritar reserves the right to explain and update the latest information.